

## JONYL FLOORING ADHESIVE – N10



### PREPARATION

The surface has to be leveled, sound, dry and clean (accordingly to BS 8203).

### APPLICATION INSTRUCTION

Application surface should be dry and dust, rust, and grease-free. Stir well before use. Apply the adhesive uniformly on the substrate using a fine trowel, brush or roller and wait for 15-20 minutes for adhesive to become tacky and then lay the floor covering. Bonding over existing floor coverings should be avoided. Clean any excess adhesive with water immediately.

### KEY FEATURES

- ✓ Environmentally safe.
- ✓ Easy application.
- ✓ Quick setting.
- ✓ Suitable to most of the surfaces.
- ✓ Good coverage.
- ✓ Heat resistant.
- ✓ Non Flammable.
- ✓ Water resistance.

### PRODUCT DESCRIPTION

**JONLY FLOORING Adhesive** is based on premium quality synthetic resin, additives, tackifier, and fine grade mineral fillers. It is acrylic water-based adhesive and compatible with most of the substrates.

### TYPICAL USES

- ✓ Multi-Purpose Floor & PVC Vinyl Adhesion.
- ✓ Bonding of PVC sheet, Vinyl coverings and tiles, EPDM sheet, Polystyrene board, PU foam and similar material with concrete, metals and wooden substrates.
- ✓ Bonding substrate with porous and non-porous surfaces.
- ✓ Floor heating installations. However, the heating should be switched off at least 48 hours before and after the installation of floor coverings.

### COVERAGE

Coverage depend upon the nature of the surface to be applied. On average, smooth surface will give First Coat - 850 gm/sq.mtr.

### PACKAGING

**JONLY FLOORING Adhesive** is available in 20 KG.

F/QC/13: R2

The information provided here is based on our test results and to the best of our current knowledge. The recommendations and suggestions here in are made to facilitate the application of the product without any guarantee or representation to results. We recommend you to ensure that the product meets all your requirements prior to the application.

**Address:** Office No 41, Jebel Ali Industrial, P.O. Box 256320, Dubai, United Arab Emirates | **Email:** info@jonleemat.com | **Website:** www.jonleemat.com

## JONYL FLOORING ADHESIVE – N10

### HEALTH AND SAFETY

As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles should be worn. Inhalation of vapor or mist should be avoided. If inhaled symptoms include coughing, wheezing, laryngitis, and shortness of breath, headache, nausea, and vomiting. Immediately shift victim to fresh air, and, if needed immediately start artificial respiration. Give oxygen if breathing is labored. Get emergency medical help. In case of eye contact, flush eyes with water for 15 minutes and call for medical help. Ingestion causes nausea, vomiting, and loss of consciousness. If accidentally swallowed do not induce vomiting rather call for medical help immediately. For skin contact, flush with water or soap and water until all traces have been removed. Seek medical attention if required.

### STORAGE AND SHELF LIFE

Store away from sunlight and preferably below 30°C. Storage should be frost protected. **JONLY FLOORING Adhesive** has 12 months shelf life if stored in required conditions.

### SHIPPING LIMITATIONS

None.

### TECHNICAL DATA

Property	Specifications
Color	Cream
Appearance	Smooth Paste
Open Time	20 to 30 (depending on ambient temperature, substrate & application)
Curing Time	48 (Approx.)
Specific Gravity	1.20 + 0.15 g/cm <sup>3</sup>
Viscosity @ 25°C (S#6,RPM#10)	20000 to 25000
Solid Content	65 + 5
Coverage (0.1-0.2mm wet film thickness)	850 (depending on type of surface and application)
Shelf Life	12

KEEP OUT OF REACH OF CHILDREN | KEEP CONTAINER TIGHTLY CLOSED | FOR INDUSTRIAL & PROFESSIONAL USE

Date: June 2023

Version: 1

Printing date: June 2023

F/QC/13: R2

The information provided here is based on our test results and to the best of our current knowledge. The recommendations and suggestions here in are made to facilitate the application of the product without any guarantee or representation to results. We recommend you to ensure that the product meets all your requirements prior to the application.

Address: Office No 41, Jebel Ali Industrial, P.O. Box 256320, Dubai, United Arab Emirates | Email: info@jonlema.com | Website: www.jonlema.com